


### ELECTRICAL CHARACTERISTICS:

1. DCR : PIN 2-3 = 127 OHM MAX.  
PIN 6-7 = 254 OHM MAX.
2. INDUCTANCE (@1KHZ, 1Vrms, W/H 80 mADC) :  
PIN 2-3 = 130 mH MIN.
3. IMPEDANCE (@650HZ, 1Vrms, W/H 80 mADC,  
PIN 6-7 W/H 600 OHM LOAD) :  
PIN 2-3 = 600 OHM %:10%.
4. INSERTION LOSS (@1KHZ, 1Vrms, W/H 80 mADC,  
PIN 6-7 w/H 600 OHM LOAD) : 3.2 dB MAX.
5. FREQUENCY RESPONSE (REF. 1KHZ) :  
@300 HZ = ±3.5 dB.  
@3.4 KHZ = ±1 dB.
6. RETURN LOSS :  
@300HZ = 5 dB MIN. W/H 80 mADC.
7. LOGITUDINAL BALANCE :  
@1KHZ = 60 dB MIN.  
@3.4KHZ = 60 dB MIN.
8. HI-PDT (@1500VAC, 1mA, 1MIN) : PRI-SCE.
9. RoHS Compliant

		 <b>Atech</b> <sup>®</sup> Atech Technology Co. Ltd. TEL:02794-6667 FAX:02794-8004		TITLE 600: 600 WET TRANSFORMER	
				DWG. NO. ATS-050BR	
		UNITS	SAFETY		SHEET 1 OF 1
		DATE	P/N:		DRAW