



ELECTRICAL CHARACTERISTICS : (671-1561 COMPATIBLE)

1. IMPEDANCE : (@1KHZ 1Vrms PIN 2-6 SHORT W/H 90mADC PIN 3-4 W/H 525 OHM LOAD)
PIN 1-5 = 600 OHM ± 10%
2. D.CR. : PIN 1-5 (W/H PIN 2-6 SHORT) = 75 OHM ± 15%
PIN 3-4 = 100 OHM ± 15%
3. INSERTION LOSS (@1KZ 1Vrms PIN 2-6 SHORT W/H 90mADC PIN 3-4 W/H 525 OHM LOAD)
PIN 1-5 = 1.6 dB MAX.
4. FREQ. RESP. (REF. 1KHZ) : @300HZ = ± 1.8dB
@600HZ = ± 0.5dB
@4KHZ = ± 0.3dB
5. RETURN LOSS (REF. 600 OHM) : @300HZ = 7.5dB MIN.
@1KHZ = 15dB MIN.
@4KHZ = 15dB MIN.
6. LOGITUDINAL BALANCE : @300-1KHZ = 70dB MIN.
@1K-4KHZ = 60dB MIN.
7. HI-POT (@1500VAC, 60HZ, 1mA, 1MINUTE) : PRI-SEC
8. RoHS COMPLIANT

						Atech [®] Atech Technology Co., Ltd. TEL: (02)2794-6667 FAX: (02)2794-8004	TITLE	TRANSFORMER
							DWG. NO.	ATS-080R
						UNITS:	SAFETY	SHEET 1 OF 1
						DATE	P/N:	DRAW