



ELECTRICAL CHARACTERISTICS: (COMPATIBLE WITH P2001 FOR V.32bis)

1. D.C.R. : PIN 1-3 = 65 OHM+/-8% PIN 6-4 = 65 OHM+/-8%
2. INDUCTANCE (@200HZ, 10mVrms, PARALLEL) : PIN 1-3 = 4.8H MIN.
3. Q(@ 200HZ, 10mVrms) : PIN 1-3 = 1.5 MIN.
4. LEAKAGE INDUCTANCE(@200HZ, 10mVrms, SERIES) : PIN 1-3 = 19mH MAX.
5. RETURN LOSS : (REF. 600 OHM) 300 TO 4KHZ = 23dB MIN.
6. INSERTION LOSS : (@1KHZ,1Vrms) 1.15dB MAX.
7. FREQ. RESPONSE: (REF. 1KHZ) 300 TO 4KHZ = +/-0.19dB
8. LONGITUDINAL BALANCE : 200HZ-4KHZ 80dB MIN.
9. TURN RATIO : (@5KHZ, 0.1Vrms) PIN 1-3 : 6-4 = 1+/-1%
10. DISTORTION : 450HZ, 0dBm : -86dB MAX.
11. HI-POT : (4000 VAC, 1mA, 1MIN.) PIN 1-6
12. CORE LOSS : (@1KHZ, 1Vrms) = 30K OHM
13. RoHS COMPLIANCE

				<b>Atech</b> <sup>®</sup>		TITLE TRANSFORMER	
				Atech Technology Co., Ltd.		DWG. NO. ATS-091R	
				TEL:(02)2794-6667 FAX:(02)2794-8004			
				UNITS:		SAFETY	
				DATE		SHEET 1 OF 1	
						DRAW	