



### ELECTRICAL CHARACTERISTICS:

- D.C.R. : PIN 1-3 = 30  $\Omega$ M $\pm$ 15% , PIN 4-6 = 38  $\Omega$ M $\pm$ 15%
- PARALLEL INDUCTANCE (@300HZ, 1Vrms) : PIN 1-3 = 1.5H MIN.
- IMPEDANCE (@1KHZ, 0dBm, 4-6 W/H 600  $\Omega$ M)  
PIN 1-3 = 600  $\Omega$ M $\pm$ 5%
- INSERTION LOSS (@1KHZ, 0dBm, 4-6 W/H 600  $\Omega$ M) : 1dB MAX.
- FREQ. RESP.(REF. 1KHZ): @300HZ =  $\pm$ 0.35dB  
@4KHZ =  $\pm$ 0.35dB
- RETURN LOSS (REF. 600  $\Omega$ M) : @300HZ = 19 dB MIN.  
@1KHZ = 22 dB MIN. @4KHZ = 23 dB MIN.
- URNS RATIO (@15KHZ, 1Vrms) : PIN 1-3 : 4-6 = 1 $\pm$ 1%
- HI-POT(1200VAC, 1mA, 1MINUTE) : PIN 1-4
- RoHS COMPLIANCE

						<b>Atech</b> <sup>®</sup> <b>Atech Technology Co., Ltd.</b> TEL: (02)2794-6667 FAX: (02)2794-8004	TITLE 600 : 600 TRANSFORMER
							DWG. NO. ATS-131R
						UNITS:	SAFETY
						DATE	P/N:
							SHEET 1 OF 1
							DRAW