



ELECTRICAL CHARACTERISTICS :

1. DCR: 1-3 = 6-4 =  $128\Omega \pm 10\%$
2. INDUCTANCE (@1KHz, 0.1Vrms) 1-3 = 0.7H MIN.
3. INSERTION LOSS (@1KHz, 0dBm) : 2.7dB TYP.
4. FREQ. RESPONSE (REF. 1KHZ)  
@200Hz =  $\pm 1\text{dB}$  @4KHz =  $\pm 1\text{dB}$ .
5. RETURN LOSS (REF. 600Ω)  
@200Hz = 14dB MIN. @4KHz = 14dB MIN.
6. TURN RATIO (@16KHz, 1Vrms) 1-3 : 6-4 =  $1 \pm 1\%$
7. THD(@600Hz, -10dBm) = -74dB TYP.
8. HI-POT (@3750VAC, 1mA, 2SEC) PRI-SEC.
9. RoHS COMPLIANT

					<b>AOEM.</b>		TITLE 600 :332 TRANSFORMER	
							DWG. NO. ATS-332R	
RELEASE					UNITS:		SAFETY	
NO: DESCRIPTION DATE BY CHK APPD					DATE		P/N: DRAW	
REVISIONS							SHEET 1 of 1	