



ELECTRICAL CHARACTERISTICS: (FOR V.90, MEET UL1950)

1. D.C.R. : PIN 1-2 = 170 OHM +/-12%. PIN 3-4 = 150 OHM +/-12%.
2. INDUCTANCE (@1KHZ, 1Vrms LP) : PIN 1-2 = 2.3Hy MIN.
3. INSERTION LOSS (@ 1KHZ, 0dBm, PIN 3-4 W/H 287 OHM)
PIN 1-2 = 3.5 dB MAX.
4. FREQ. RESP.(REF. 1KHZ) : @200HZ-4KHZ = +/-0.2dB
5. RETURN LOSS (REF. 600 OHM) : @ 200HZ - 4KHZ = 25dB MIN.
6. TURNS RATIO : PIN 1-2 : PIN4-3 = 1+/-1%
7. LONGITUDINAL BAL. = 60dB MIN.(@200-4KHZ)
8. T.H.D. (@600HZ, -10dBm) = -80dB TYP.
9. HI-POT (@1650VAC, 1mA, 2SEC.) PRI. - SEC.
10. RoHS COMPLIANCE

					Atech [®]		TITLE 600 : 287 TRANSFORMER	
					Atech Technology Co., Ltd.		DWC. NO.	
					TEL:(02)2784-8857 FAX:(02)2784-8804		ATS-348BR	
					UNITS:		SAFETY	
					DATE		P/N:	
					REVISIONS		SHEET 1 of 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW