



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN 1-3 = 6-4 = 113 OHM ± 12%
2. INDUCTANCE (@250HZ, 1Vrms, PARALLEL) : PIN 1-3 = 14H MIN.
3. RETURN LOSS : (REF. 600 OHM) 200 TO 4KHZ = 30dB MIN.
4. INSERTION LOSS : (@1KHZ,0dBm) PIN 1-3 = 2.1 ± 0.3 dB
5. FREQ. RESPONSE : (REF. 1KHZ) 200 TO 4KHZ = ± 0.2 dB
6. LONGITUDINAL BALANCE : 200 HZ - 4KHZ 80 dB MIN.
7. TURN RATIO : (11KHZ, 1Vrms) PIN 1-3 : 6-4 = 1 ± 1%
8. HI-POT : (@1500V, 5mA, 2SEC) PRI-SEC
9. RoHS COMPLIANCE.

					Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8867 FAX:(02)2794-8004		TITLE 600: 374 TRANSFORMER	
							DWG. NO. ATS-369AR	
RELEASE					UNITS:		SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1
REVISIONS							DRAW	