



ELECTRICAL CHARACTERISTICS :

- 1 D.C.R. : PIN 1-3 = 78 ΩHM ± 15%
PIN 4-6 = 105 ΩHM ± 15%
- 2 INDUCTANCE : (AT 1KHZ, 1Vrms) PIN 1-3 = 400mH MIN. (W/O DC)
PIN 1-3 = 200mH MIN. (W/H 80mA DC)
- 3 IMPEDANCE = 600 ΩHM ± 15%
(AT 1KHZ, 1Vrms, 0-80mA DC, PIN 4-6 W/H 600 ΩHM)
- 4 INSERTION LOSS = 1.7db MAX. (AT 1KHZ, 1Vrms, W/H 600 ΩHM LOAD)
- 5 FREQ. RESP. = ± 0.5db (300HZ -3.4KHZ, REF. TO 1KHZ)
- 6 RETURN LOSS : ERL = 14db MIN.
SRL-LD = 8db MIN.
SRL-HI = 16db MIN.
- 7 LOGITUDINAL BALANCE = 60db MIN. (AT 1KHZ)
LOGITUDINAL BALANCE = 60db MIN. (AT 3.4KHZ)
- 8 HI-POT = 1500VAC, 1mA, 1MINUTE (PRI-SEC-CORE)
- 9. RoHS COMPLIANT

				Atech [®]		TITLE TRANSFORMER	
				Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004		DWG. NO. ATS-001R	
				UNITS:		SAFETY	
				DATE		SHEET 1 OF 1	
				P/N:		DRAW	