



ELECTRICAL CHARACTERISTICS : <COMPATIBLE WITH P1200 FOR V.32bis>

1. D.C.R. : PIN 1-3 = 6-4 = 65 OHM ± 5%
2. INDUCTANCE (@200HZ, 10mVrms, PARALLEL) : PIN 1-3 = 4.15H MIN.
3. LEAKAGE INDUCTANCE (@200HZ, 10mVrms, SERIES) : PIN 1-3 = 20mH MAX.
4. RETURN LOSS : (REF. 600 OHM) 300HZ = 21dB MIN.
1KHZ = 21dB MIN.
4KHZ = 21dB MIN.
5. INSERTION LOSS : (@1KHZ, 1Vrms) 1-3 = 1.3dB MAX.
6. FREQ. RESPONSE : (REF. 1KHZ) 300 TO 4KHZ = ± 0.5dB
7. TURN RATIO : (@6KHZ, 0.1Vrms) PIN 1-3 : 6-4 = 1 ± 1%
8. DISTORTION : 300HZ, 0dbm : -77dB MAX.
9. HI-POT : (<3750VAC, 1mA, 1MIN.) PIN 1-6
10. RoHS COMPLIANCE.

								TITLE	
								TRANSFORMER	
						Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004		DWG. NO.	
								ATS-079R	
						UNITS:		SAFETY	
						DATE		P/N	
								DRAW	