


PIN 4,6,10 CUT OFF

Unit:mm



ELECTRICAL CHARACTERISTICS:

- 1.DCR : PIN 1-2 = 180mΩ MAX.
PIN 3-5 = 1.5Ω MAX.
PIN 7-8 = 60mΩ MAX.
PIN 9-7 = 150mΩ MAX.

- 2.INDUCTANCE (@10KHz,1.0Vrms):
PIN 3-5 = 580uH ±10%

- 3.LEAKAGE INDUCTANCE (@100KHz, 1.0Vrms):
PIN 3-5 (PIN 1-2,7-8-9 SHORT) = 35uH MAX.

- 4.TURN RATIO : (@100KHz, 0.1Vrms):
PIN 3-5 : 1-2 = 7.78±2%
PIN 3-5 : 7-8 = 18.16±2%
PIN 3-5 : 9-7 = 13.62±2%

- 5.HI-POT : (@3000VAC, 3mA, 3SEC) PIN3.1 - PIN9

- 6.RoHS COMPLIANT

					AOEM.		TITLE	TRANSFORMER
							DWG. NO.	ATS-1285R
					UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS								