



ELECTRICAL CHARACTERISTICS:

- DCR : PIN 1-2 = 75mΩ MAX
PIN 4-5 = 165mΩ MAX
PIN 6.7-9.10 = 12.5mΩ MAX
- INDUCTANCE (@250kHz, 0.1Vrms) :
PIN 1-2 = 40uH ±10%
- LEAKAGE INDUCTANCE (@250kHz, 0.1Vrms)
PIN 1-2 (PIN 4-5, PIN 6.7 - 9.10 SHORT) = 0.56uH MAX.
- TURN RATIO (@100kHz, 0.1Vrms)
PIN 1-2 : PIN 6.7 - 9.10 = 2.5 ±2%
PIN 1-2 : PIN 4-5 = 2.5 ±2%
- HI-POT : (@1500VAC ,1mA, 2SEC) PIN 1.4 - PIN 6.7
- OPERATING TEMPERATURE : -40°C~+125°C
- RoHS COMPLIANT

								TITLE FLYBACK TRANSFORMER	
								DWG. NO. ATS-1549R	
RELEASE						UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW	
REVISIONS									