



ELECTRICAL CHARACTERISTICS:

1. DCR : PIN 1.2 – 3.4 = 45mΩ MAX.  
PIN 5-6 = 155mΩ MAX.  
PIN 7.8.9 – 10.11.12 = 9mΩ MAX.
2. INDUCTANCE (@200kHz, 0.1Vrms) : PIN 1.2 – 3.4 = 18uH ±10%
3. LEAKAGE INDUCTANCE (@100kHz, 0.1Vrms)  
PIN 1.2 – 3.4 (PIN 5-6, PIN 7.8.9 – 10.11.12 SHORT) = 0.8uH MAX.
- △ 4. TURN RATIO (@100kHz, 1Vrms)  
PIN 1-3 : PIN 2-4 = 1.0 ±2%  
PIN 1-3 : PIN 5-6 = 2.29 ±2%  
PIN 1-3 : PIN 10.11.12 – 7.8.9 = 2.66±2%
5. HI-POT (@1500VAC, 1mA, 2SEC) PIN 1.2.5 – PIN 10.11.12
6. OPERATING TEMPERATURE : -40°C~+125°C
- △ 7. STORAGE TEMPERATURE RANGE : -25°C~+85°C
8. RoHS COMPLIANT

					<b>AOEM.</b>		TITLE FLYBACK POWER TRANSFORMER	
							DWG. NO. ATS-1726R	
RELEASE					UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS								