



ELECTRICAL CHARACTERISTICS (P2781 COMPATIBLE)

1. DCR: 1-3 = 6-4 = 112 OHM +/- 10%
2. INDUCTANCE (@1KHZ, 0.1Vrms, PARALLEL)
1-3 = 1.6H MIN.
3. INSERTION LOSS (@2KHZ, 1Vrms) : 2dB MAX.
4. FREQ. RESPONSE (REF. 2KHZ)
@200HZ = +/- 0.2dB @4KHZ = +/- 0.1dB.
5. RETURN LOSS (REF. 600 OHM)
@200HZ = 18dB MIN. @4KHZ = 24dB MIN.
6. TURN RATIO (@1KHZ, 1Vrms) 1-3 = 6-4 = 1+/-1%
7. HI-POT (@3750VAC, 1mA, 2SEC) PRI-SEC.
8. WORKING TEMP. : -10°C TO +70°C
9. RoHS COMPLIANCE.

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004	TITLE TRANSFORMER	
							DWG. NO. ATS-311R	
						UNITS:	SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	SHEET 1 OF 1 DRAW
REVISIONS								