



ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-2 = 2.37 KOHM MAX.
PIN 4-3 = 2.82 KOHM MAX.
2. INDUCTANCE PARALLEL (@250HZ, 0.5Vrms) : PIN 1-2 = 70H MIN.
3. INSERTION LOSS (@1KHZ, 1Vrms, PIN 4-3 W/H 20KOHM) :
PIN 1-2 = 1.3dB ± 0.25dB
4. FREQ. RESP. (@REF 1KHZ) : @300HZ = ±0.3dB
@4KHZ = ±0.3dB
5. RETURN LOSS (@REF 20KOHM) : @300HZ = 18dB MIN.
@1KHZ = 18dB MIN.
@4KHZ = 18dB MIN.
6. TURN RATIO (@12KHZ, 1Vrms) : PIN 1-2 : PIN 4-3 = 1 ± 1%
7. HI-POT (@1250VAC, 1mA, 2SEC) : PIN 1-4
8. RoHS COMPLIANT

| | | | | | | | |
|-----------|-------------|------|----|-----|------|---|--------------------------------|
| | | | | | | Atech [®] Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004 | TITLE 20K : 20K TRANSFORMER |
| | | | | | | | DWG. NO. ATS-667R |
| REVISIONS | | | | | | UNITS: | SAFETY |
| NO. | DESCRIPTION | DATE | BY | CHK | APPD | DATE | SHEET 1 OF 1 DRAW |