

Adapter A0871TD-240030



Features

- Meet DoE Level VI
- High Reliability
- Application: Telecom, Set top box, modems, IT

Characteristics

Output Wattage	87W	Load Regulation	±5% @ 5.1V3A, ±10% @ 24V3A
Output Voltage	5.1V, 24V	Ripple & Noise	100mVp-p Max @ 5.1V3A, 300mVp-p Max @ 24V3A
Output Current	3A, 3A	Efficiency	86% min @ 115Vac/230Vac, DOE Level VI
Input Voltage	115Vac/230Vac (100~240Vac min/max)	Surge	±1KV(L-L), ±2KV(L-G), EN61000-4-5, Criteria B
Input Current	3A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air ±8KV, Contact ±4KV EN61000-4-2
Leakage Current(A)		MTBF	50000Hrs min. @ 115Vac/230Vac, 80% load, 25°C (Telcordia SR-332, issue 2)
No Load Power Consumption	<0.3W @ 115Vac/230Vac		

Environmental

Safety

Operating Temperature	0°C ~ +40°C	Meet CE
Storage Temperature	-40°C ~ +85°C	
Humidity	20% ~ 95%	

Dimension Diagram Unit:mm

