



Tolerance: +/- 0.3mm

ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-3 = 4-6 = 1.62 KOHM ± 15%.
2. INDUCTANCE PARALLEL (@1KHZ, 0.1Vrms) : PIN 1-3 = 25H MIN.
3. INSERTION LOSS (@2KHZ, 1Vrms 4-6 W/H 10KOHM) :
PIN 1-3 = 2dB MAX.
4. FREQ. RESP. (@REF 2KHZ) : @200HZ = ± 0.5dB
@4KHZ = ± 0.2dB.
5. RETURN LOSS (@REF 10KOHM) : @200HZ = 14dB MIN.
@4KHZ = 14dB MIN.
6. TURN RATIO (@7.9KHZ, 1Vrms) : PIN 1-3 : PIN 6-4 = 1 ± 1%
7. HI-POT (@3750VAC, 1mA, 2SEC) : PRI-SEC
8. RoHS COMPLIANCE.

						Atech [®]		TITLE 10K : 10K TRANSFORMER	
						Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004		DWG. NO. ATS-630R	
REVISIONS						UNITS:		SAFETY	
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	SHEET 1 OF 1	
								DRAW	