



### ELECTRICAL CHARACTERISTICS :

(64KBps INTERFACE FOR G.703)

1. HIPOT : 1500Vrms
2. TURNS RATIO : 1 : 2CT  $\pm$  3% (PIN 1-3 : PIN 4-5-6)
3. OCL (PIN 1-3) : 20mH MIN. @10KHZ 100mV
4. CW/W (PRI.-SEC.) : 130pF MAX. @100KHZ 100mV
5. D.C.R. (PIN 1-3) : 2.65 OHMS MAX.
6. D.C.R. (PIN 6-4) : 5.0 OHMS MAX.
7. LEAKAGE INDUCTANCE (PIN 1-3) : 5uH MAX. @100KHZ, 100mV  
PIN 4-6 SHORTED

						 <b>Atech</b> <sup>®</sup> Atech Technology Co., Ltd. TEL:0212794-6667 FAX:0212794-8004	TITLE 64KBPS TRANSFORMER DWG. NO. ATPL-002	
A	CHAMFER	10/21/98	PAIR		SUEDY		UNITS: M/M SAFETY	SHEET 1 OF 1 DRAW Pair
	RELEASE	09/04/97	PAIR		SUEDY			
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		
REVISIONS						09/04/97		