



ELECTRICAL CHARACTERISTICS : (PE-64995 COMPATIBLE)

- D.C.R. : PIN 1-3 = 2.5 OHM \pm 25%
PIN 4-6 = 4.3 OHM \pm 25%
- INDUCTANCE : (@10KHZ, 50mV, SERIES) PIN 1-3 = 22mH MIN.
- INTERWINDING CAP. : (@100KHZ, 50mV) PIN 1-6 = 100pF MAX.
- LEACKAGE INDUCTANCE : (@100KHZ, 50mV, PIN 1-3 SHORT)
PIN 4-6 = 15uH MAX.
- TURNS RATIO : (@30KHZ, 1Vrms) PIN 4-6 : PIN 1-3 = 2 \pm 2%
- HI-POT : (@2KVAC, 2SEC) PRI.-SEC.

UNLESS OTHERWISE SPECIFIED ALL TOLERANCES ARE ± 0.25

D	DIM.	02/16/2005	BART	AL	SUEDY	 Atech [®] Atech Technology Co., Ltd. TEL:02(2)794-6667 FAX:02(2)794-8004	TITLE	ISDN-S TRANSFORMER	
C	DCR.	12/28/00	PAIR		SUEDY		DWG. NO.	ATPL-004	
B	PIN.	12/14/99	PAIR		SUEDY		UNITS:	M/M	
	RELEASE	12/22/97	PAIR		SUEDY	DATE	12/22/97	SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD			SHEET 1 OF 1	
REVISIONS								DRAW	<i>Patr</i>