



ELECTRICAL CHARACTERISTICS: (PE-85508 COMPATIBLE)

1. D.C.R. : 0.2 OHM MAX. (EACH WINDING)
2. INDUCTANCE : (@100KHZ, 50mV) = 7.6uH MIN.
3. LEAKAGE INDUCTANCE : (@100KHZ, 50mV)
 PIN 1-3 (PIN 14-16 SHORT) = 0.1 uH MAX.
 PIN 6-8 (PIN 9-11 SHORT) = 0.1uH MAX.
4. INTERWINDING CAP. : (@100KHZ, 50mV)
 PRI. - SEC. = 5pF MAX.
5. TURNS RATIO : PIN 1-3 : PIN 16-14 = 1 : 1
 PIN 6-8 : PIN 11-9 = 1 : 1
6. HI-POT : (@2000 VAC, 1mA, 2SEC.) PRI. -SEC.

						Atech [®]		TITLE FIBER CHANNEL TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO.	
						TEL:(02)2794-6667 FAX:(02)2794-6004		ATPL-015	
RELEASE		07/14/98	PAIR		SUEDY	UNITS:	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APP'D	M/M			DRAW
REVISIONS						DATE			Pair
						07/14/98			