



ELECTRICAL CHARACTERISTICS: (PE-65499, COMPATIBLE)

- D.C.R. : PRI. = 1.5 OHM MAX. SEC. = 3.0 OHM MAX.
- INDUCTANCE (@10KHZ, 100mVrms) :
 1-4 (2-3 SHORT) = 22mH MIN.
 5-8 (6-7 SHORT) = 22mH MIN.
- LEACKAGE INDUCTANCE (@100KHZ, 100mVrms) :
 13-16 (2-3, 1-4, 14-15 SHORT) = 11uH MAX.
 9-12 (6-7, 5-8, 10-11 SHORT) = 11uH MAX.
- INTERWINDING CAP. (@100KHZ, 100mVrms) :
 PRI. - SEC. = 100 pF MAX.
- TURNS RATIO (@10KHZ, 100mVrms)
 PRI : SEC = 1 : 2 +/- -2%
- HI-POT (2KVAC, 1mA, 2SEC) : PRI. - SEC.

					 Atech Technology Co., Ltd. <small>TEL (02)2704-6667 FAX(02)2704-8004</small>		TITLE ISDN-S TRANSFORMER	
B	23.5/14/10.9/DCR	10/26/00	PAIR	SUEDY			DWG. NO. ATPL-018	
A	PIN=3.0+/-0.35	4/22/99	PAIR	SUEDY	UNITS: M/M		SHEET 1 OF 1	
RELEASE		08/10/98	PAIR	SUEDY	SAFETY		DRAW	
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE	Pair	
REVISIONS					08/10/98			