



ELECTRICAL CHARACTERISTICS: (PE-65498 COMPATIBLE)

1. D.C.R. : PRI. = 2.5 OHM+/-25% SEC. = 5.8 OHM+/-25%
2. INDUCTANCE ( @10KHZ, 100mVrms) : PIN1-4, PIN5-8 = 22mH MIN.
3. LEAKAGE INDUCTANCE ( @100KHZ, 100mVrms) : 8-40uH ( @PRI SHORTED)
4. INTERWINDING CAP. ( @100KHZ, 100mVrms) : PRI. - SEC. = 100 pF MAX.
5. TURNS RATIO ( @10KHZ, 100mVrms) A : B : C : D = 1 : 1 : 2.5 : 2.5 +/-2%
6. ISOLATION : 2000Vrms
7. WAVE SOLDERING TEMPERATURZ : 245 +/- 10 DEGC.

						 <b>Atech</b> <sup>®</sup> <b>Atech Technology Co., Ltd.</b> TEL (02)2704-6667 FAX(02)2704-8004	TITLE ISDN-S TRANSFORMER		
A PIN=3.0+/-0.35							4/22/99	PAIR	SUEDY
RELEASE						08/15/98	PAIR	SUEDY	UNITS: M/M SAFETY
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE	08/15/98	SHEET 1 OF 1	
REVISIONS								DATE	DRAW <i>Pair</i>