



ELECTRICAL CHARACTERISTICS : @25°C (PE-65865 COMPATIBLE)

1. ISOLATION : 1500Vrms (PRI TO SEC)
2. TURNS RATIO : (PIN16-14) : (PIN1-2-3) = 1 : 1.15CT ±5%
3. TURNS RATIO : (PIN6-7-8) : (PIN11-10-9) = 1CT : 2CT ±5%
4. PRI DCL : 1.2mH MINIMUM @100KHz 50mV
5. Cw/w : 30pF MAXIMUM @100KHz 50mV (PRI/SEC)
6. LEAKAGE INDUCTANCE : 0.6µH MAX. @100KHz 50mV  
PIN16-14 (PIN1-3 SHORTED)  
PIN6-8 (PIN11-9 SHORTED)
7. PRI DC RESISTANCE : 0.70 OHMS MAXIMUM
8. PIN1-3 DC RESISTANCE : 0.7 OHMS MAXIMUM
9. PIN11-9 DC RESISTANCE : 1.0 OHM MAXIMUM

						<b>Atech</b> <sup>®</sup>		TITLE T1/E1/ISDN TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATPL-053	
						TEL:(02)2794-6667 FAX:(02)2794-8004			
RELEASE		D2/26 /99	PAIR		SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW Pair
REVISIONS						02/26/99			