



ELECTRICAL CHARACTERISTICS: (PE-68646 COMPATIBLE)

- HIPOT : 3000Vrms (PRI - SEC)
- URNS RATIO : 1 : 1.58 +/-5% (PIN 10-6 : PIN 3-5)
1 : 2 +/-5% (PIN 10-6 : PIN 1-5)
- CL (PIN 10-6) : 1.5mH MIN. @100KHZ 50mV
- CW/W (PRI.-SEC.) : 20pF MAX. @100KHZ 50mV
- D.C.R. (PIN 10-6) : 0.7 □HMS MAX.
- D.C.R. (PIN 1-5) : 1.4 □HMS MAX.
- LEAKAGE INDUCTANCE (PIN 10-6) : 0.7uH MAX. @100KHZ, 50mV @SEC SHORTED

UNLESS OTHERWISE SPECIFIED ALL TOLERANCES ARE ±0.25

					Atech [®]		TITLE T1/E1/ISDN TRANSFORMER	
B	DIM.	02/16/2005	BART	AL	SUEDY	Atech Technology Co., Ltd.		DWG. NO. ATPL-063
A	H = 10.25 MAX.	04/30/2003	RDRY	PAIR	SUEDY	TEL:(02)2794-6667 FAX:(02)2794-8004		
	RELEASE	03/16/99	PAIR		SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>
REVISIONS						03/16/99		