



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : 1-4 = 5-8 = 4 OHM MAX.(2-3, 6-7 SHORT)  
13-16 = 9-12 = 5.5 OHM MAX.(14-15 , 10-11 SHORT)
2. INDUCTANCE : (@10KHZ, 0.1Vrms, 2-3, 6-7 SHORT)  
1-4 = 5-8 = 22mH MIN.
3. LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms)  
1-4 = 5-8 = 10uH MAX.(2-3,14-15,13-16,6-7,10-11,9-12 SHORT)
4. INTERWINDING CAP.:(@10KHZ,0.1Vrms)  
PRI - SEC = 120pF MAX.
5. TURNS RATIO : (@15KHZ, 0.1Vrms)  
1-2 : 3-4 : 14-13 : 16-15 = 1 : 1 : 2 : 2  
5-6 : 7-8 : 10-9 : 12-11 = 1 : 1 : 2 : 2
6. HI-POT : (@2000Vrms, 1mA 2SEC.)  
BETWEEN EACH WINDING

						<b>Atech</b> <sup>®</sup>		TITLE ISDN SD MODULE		
B PIN ASSIGNMENT						11/02/99	PAIR	SUEDY	Atech Technology Co., Ltd. TEL:(02)2794-8887 FAX:(02)2794-8884	
A ADD PIN #5,#14						10/29/99	CVFENG	SUEDY	DWG. NO. ATPL-078A	
RELEASE						09/04/99	PAIR	SUEDY	UNITS M/M	SAFETY
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1		
REVISIONS						09/04/99		DRAW <i>Pair</i>		