



ELECTRICAL CHARACTERISTICS : (PT5069, COMPATIBLE)

- D.C.R. : PRI. = 2.5 OHM MAX.
SEC. = 5.0 OHM MAX.
- INDUCTANCE (@10KHZ, 100mVrms) : PIN 1-4 (2-3 SHORT) = 22mH MIN.
PIN 5-8 (6-7 SHORT) = 22mH MIN.
- LEACKAGE INDUCTANCE (@100KHZ, 100mVrms) :
PIN 1-4 (2-3, 13-16, 14-15 SHORT) = 5uH MAX.
PIN 5-8 (6-7, 9-12, 10-11 SHORT) = 5uH MAX.
- INTERWINDING CAP. (@100KHZ, 100mVrms) : PRI. - SEC. = 85pF MAX.
- URNS RATIO (@10KHZ, 100mVrms) : PRI : SEC = 1 : 2 ± 2%
- HI-PDT (2KVAC, 1mA, 2SEC) : PRI. - SEC.

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004	TITLE ISDN-S TRANSFORMER	
							DWG. NO. ATPL-085	
A	10.80 MAX.	01/15 /2003	DOLLY	AL	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1 DRAW <i>Pair</i>
	RELEASE	01/11 /00	RORY		SUEDY			
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		
REVISIONS						01/11/00		