


GRID 2.54 X 2.54



### ELECTRICAL CHARACTERISTICS :

- 1 D.C.R. : PIN 1-2 = 92mΩ MAX.  
PIN 3-4 = PIN 4-5 = 315 mΩ MAX.
- 2 INDUCTANCE (AT 10KHZ, 120mVrms) : PIN 1-2 = 495uH MIN.
- 3 INTERWINDING CAPACITANCE (AT 10KHZ, 120mVrms) :  
PIN 1-3 = 20pF MAX. (PIN 1-2 SHORT, PIN 3-4-5 SHORT)
- 4 LEAKAGE INDUCTANCE (AT 10KHZ, 120mVRMS) :  
PIN 1-2 = 4uH MAX. (PIN 3-4-5 SHORT)
- 5 TURN RATIO : PIN 1-2 : PIN 3-4 : PIN 4-5 = 1.2 : 1 : 1
- 6 HI-POT (1KVAC, 1mA, 1 MINUTE) : PRI-SEC-CORE

					<b>Atech®</b>		TITLE TRANSFORMER	
					Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		DWG. NO. ATS-021	
RELEASE			PAIR	SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW Pair	
REVISIONS					E159603			