



ELECTRICAL CHARACTERISTICS :

<671-5792 COMPATIBLE>

1. D.C.R. : PIN 1-3 = 0.8 Ω HM MAX.
PIN 4-6 = 0.8 Ω HM MAX.
2. INDUCTANCE (@10KHZ, 0.2Vrms) : PIN 1-3 = 3mH MIN.
3. INTERWINDING CAP (@10KHZ, 0.2Vrms) : PIN 1-6 = 27pF MAX.
4. INSERTION LOSS :
(@772KHZ, 1Vrms, 4-6 W/H 100 Ω HM) 0.2dB MAX.
5. FREQ. RESP (REF. 722KHZ) : @100KHZ = ± 0.1 dB
@1.544MHZ = ± 0.1 dB
6. RETURN LOSS (REF. 100 Ω HM) : @100KHZ-2MHZ = 18dB MIN.
7. TURNS RATIO (@50KHZ, 1Vrms) : PIN 1-3 : 6-4 = $\pm 1\%$
8. HI-POT (@1200VAC, 1mA, 2SEC) PRI-SEC

					Atech®		TITLE T1/E1 TRANSFORMER	
					Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		DWG. NO. ATS-265	
A	RETURN LOSS	01/10 /2003	DOLLY	SIMON	SUEDY	UNITS: INCH	SAFETY	SHEET 1 OF 1
	RELEASE	10/23 /97	PAIR		SUEDY	DATE		
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>
REVISIONS						10/23/97		