



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN1-3 = 460 mOHM MAX. PIN 4-6 = 650 mOHM MAX.
2. INDUCTANCE (@1KHZ, 0.1Vrms,LS) PIN 1-3 = 1.5mH MIN.
3. INSERTION LOSS:(@1.544MHZ, -10dBm, 120 OHM LOAD)
PIN 1-3 = 0.25dB MAX.
4. FREQ. RESP(REF. 1.544MHZ)
@20KHZ = +/-0.25dB @3MHZ = +/-0.25dB
5. RETURN LOSS: (REF. 75 OHM,@1.544MHZ)
PIN 1-3 = 20dB MIN.
7. TURNS RATIO:(@10KHZ, 0.1Vrms) 6-4 : 1-3 = 1.263 +/-1%
8. HI-POT (@1KVAC, 1mA, 2SEC) PRI-SEC

						Atech [®]		TITLE 75:120 TI/EI TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-288	
						TEL:(02)2794-6667 FAX:(02)2794-8004			
RELEASE	06/03/98	PAIR		SUEDY	UNITS M/M	SAFETY		SHEET 1 OF 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW <i>Pair</i>
REVISIONS						06/02/98			