



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : 2-17 = 4-15 = 4 OHM MAX.
9-10 = 8-11 = 5.5 OHM MAX.
1-2 = 17-18 = 4-5 = 14-15 = 1.3 OHM MAX.
2. INDUCTANCE : (@10KHZ, 0.1Vrms)
2-17 = 4-15 = 22mH MIN.
1-2 = 17-18 = 4-5 = 14-15 = 5mH +50/-30%
3. LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 9-10,8-11 SHORT)
2-17 = 4-15 = 4uH MAX.
4. CHOKE LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 17-18, 14-15 SHORT)
1-2 = 4-5 = 0.6uH MAX.
5. INTERWINDING CAP.:(@10KHZ,0.1Vrms)
1-9 = 5-8 = 120pF MAX.
6. TURNS RATIO : (@15KHZ, 0.1Vrms)
9-10 : 2-17 = 2+/-1%
8-11 : 4-15 = 2+/-1%
1-2 : 18-17 = 5-4 : 14-15 = 1+/-1%
7. HI-POT : 2-9, 4-8 (@3000Vrms, 1mA 2SEC.)
3-16 (@500Vrms, 1mA,2SEC, 1-9, 5-8 SHORT)

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8867 FAX:(02)2794-8004	TITLE ISDN SO MODULE	
B	H= 14.4 MAX.	08/22/98	PAIR		SUEDY		DWG. NO ATS-302	
A	LEAKAGE 4-5	07/04/98	PAIR		SUEDY	UNITS M/M		
	RELEASE	06/23/98	PAIR		SUEDY	SAFETY		
NO:	DESCRIPTION	DATE	BY	CHK	APPD	SHEET 1 OF 1		
REVISIONS						DATE 06/23/98		DRAW <i>Pair</i>