



ELECTRICAL CHARACTERISTICS:

- D.C.R. : 2-17 = 4-15 = 3.0 OHM MAX.
9-7 = 10-12 = 6.0 OHM MAX.
1-2 = 17-18 = 4-5 = 14-15 = 1.0 OHM MAX.
- INDUCTANCE : (@10KHZ, 0.1Vrms)
2-17 = 4-15 = 22 mH MIN.
1-2 = 17-18 = 4-5 = 14-15 = 5mH +50/-30%
- LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 9-7,10-12 SHORT)
2-17 = 4-15 = 5uH MAX.
- CHOKE LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 17-18, 14-15 SHORT)
1-2 = 4-5 = 0.6uH MAX.
- INTERWINDING CAP.(@10KHZ,0.1Vrms)
1-9 = 5-10 = 150pF MAX.
- URNS RATIO : (@15KHZ, 0.1Vrms)
9-7 : 2-17 = 2+/-1%
10-12 : 4-15 = 2+/-1%
1-2 : 18-17 = 5-4 : 14-15 = 1+/-1%
- HI-POT : 2-9, 4-10 (@2000Vrms, 1mA 2SEC.)
3-16 (@500Vrms, 1mA,2SEC, 1-9, 5-10 SHORT)

						 Atech Technology Co., Ltd. TEL:(02)2784-8867 FAX:(02)2784-8804		TITLE ISDN	
								SO MODULE	
								DWG. NO.	
								ATS-405	
RELEASE	09/02/99	PAIR		SLEDDY	UNITS:	SAFETY		SHEET 1 OF 1	
NO. DESCRIPTION	DATE	BY	CHK	APPJ	M/M			DRAW	
REVISIONS					DATE			Pair	
					09/02/99				