


ELECTRICAL CHARACTERISTICS:

1. DCR = 10-6 = 2.9 OHM MAX. (<@2-4 SHORT> 1-5 = 5.8 OHM MAX.
2. INDUCTANCE : (<@10KHZ , 100 mVrms>) PIN 10-6 = 22 mH MIN.
3. CW/W : (<@10KHZ , 100 mVrms , 2-4 SHORT>) PIN 10-1 = 80 pF MAX.
4. CD : (<@1 MHZ , 1 V>) PIN 10-6 = 22 pF MAX.
5. LS : (<@100KHZ , 100 mV , 2-4 , 1-5 SHORT>) 10-6 = 5uH MAX.
6. TURNS RATIO : (<@10 KHZ , 100mV , 2-4 SHORT>) 1-5 : 10-6 = 2±1%
7. HI - POT : (<@1.5 KVrms , 2 SEC , 2-4 SHORT>) 10-1

C	4.7 MAX.	06/08/00	FENG		SUEDY	 Atech Technology Co., Ltd. <small>TEL:(02)2794-6667 FAX:(02)2794-8004</small>	TITLE ISDN-S TRANSFORMER
B	ADD MARKING	02/21/00	PAIR		SUEDY		DWG. NO. ATS-416
A	ADDELETRICALCHR.	01/24/00					
	RELEASE	10/07/99	PAIR		SUEDY	UNITS: M/M	SAFETY
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	SHEET 1 OF 1
REVISIONS						10/07/99	DRAW <i>Pair</i>