



ELECTRICAL CHARACTERISTICS:(FOR MITEL 8903 MEET IEC 950)

- D.C.R. : 8-19 = 7-20 = 6-21 = 5-22 = 0.2 OHM TYP.  
1-26 = 2-25 = 3.4 OHM TYP.  
13-14 = 12-15 = 11-16 = 10-17 = 1.0 OHM TYP.
- INDUCTANCE : (@10KHZ, 0.1Vrms)  
8-20 = 6-22 = 30mH MIN.(7-19 , 5-21 SHORT)  
13-14 = 12-15 = 11-16 = 10-17 = 5mH +50/-30%
- LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 7-19,2-25,5-21,1-26 SHORT)  
8-20 = 6-22 = 5uH MAX.
- CHOKER LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 12-15 SHORT)  
13-14 = 0.6uH MAX.
- INTERWINDING CAP.:(@10KHZ,0.1Vrms)  
PRI-SEC =45pF MAX.
- TURNS RATIO : (@15KHZ, 0.1Vrms)  
8-19 : 7-20 : 2-25 =1 : 1 : 4±2%  
6-21 : 5-22 : 1-26 =1 : 1 : 4±2%  
13-14 : 12-15 = 11-16 : 10-17 = 1±1%
- HI-POT : PRI-SEC (@3000Vrms, 1mA 2SEC.)

						<b>Atech</b> <sup>®</sup>		TITLE ISDN SO MODULE	
						Atech Technology Co., Ltd.		DWG. NO. ATS-435	
						TEL:(02)2794-6667 FAX:(02)2794-8004			
RELEASE	12/24/99	PAIR		SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW Pair		
REVISIONS						12/24/99			