



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : 1-5 (2-4 SHORT) = 7.4 OHM MAX. 9-6 = 4.4 OHM MAX.
2. INDUCTANCE : (@1KHZ, 50mV, W/H 2-4 SHORT) 1-5 = 15.5 mH±16%
1-5(W/H 50 mADC) = 13.5mH MIN.
3. TURNS RATIO : 1-2 : 4-5 = 1±1%
1-5 : 6-9 (2-4 SHORT) = 1.657±1%
4. RETURN LOSS : (REF 135 OHM) W/H 43 OHM. @10KHZ = 20dB MIN.
@25KHZ = 20dB MIN.
5. HI-POT : (@1500VAC, 1mA, 1MIN) 1-6.

| | | | | | | | | |
|-----------|-------------|------|----|-------|---|------------------|------------------------------------|--|
| | | | | | Atech Technology Co., Ltd. <small>TEL:(02)2794-8867 FAX:(02)2794-8004</small> | | TITLE ISDN U-INTERFACE TRANSFORMER | |
| | | | | | | | DWG. NO. ATS-445 | |
| RELEASE | 03/08/00 | PAIR | | SUEDY | UNITS: M/M | SAFETY | | |
| NO: | DESCRIPTION | DATE | BY | CHK | APPD | DATE | SHEET 1 of 1 | |
| REVISIONS | | | | | 03/08/00 | DRAW <i>Pair</i> | | |