



ELECTRICAL CHARACTERISTICS : (FOR ETE 13K38AY COMPATIBLE)

1. D.C.R : 6-7=9-10=1.87±12% 1-2=4-5=0.88±12%
2. INDUCTANCE : (@1KHZ, 0.1Vrms, 7-9 SHORT) 6-10=6.4mH±20%
3. LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms, 7-9, 6-10, 2-4 SHORT) 1-5=30uH MAX.
4. INTERWINDING CAP. : (@10KHZ, 0.1Vrms, 7-9, 2-4 SHORT) 1-10=65pF MAX.
5. TURN RATIO : (@5KHZ, 1Vrms) 6-10(7-9 SHORT):1-5(2-4 SHORT)=2±1%
1-2:4-5=1±1% 6-7:9-10=1±1%
6. HI-POT : (@1250VAC, 1mA, 2SEC) PRI-SEC.

						Atech [®]		TITLE ISDN TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-465	
						TELE:(02)2794-6667 FAX:(02)2794-8004			
RELEASE	08/01/00	FENG		SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW		Pair
REVISIONS						08/01/00			