



ELECTRICAL CHARACTERISTICS :

(FOR APPLICATIONS WITH 2B1Q AND 4B3T CODING, PE-68669 COMPATIBLE)

- D.C.R. : PIN 1-2 = 3-4 = 2.6 OHM ± 15%
PIN 5-7 = 3.2 OHM ± 15%
- INDUCTANCE (@1KHZ, 0.1Vrms, 2-3 SHORT, W/H 50mAC) :
PIN 1-4 = 15.5mH ± 16%
- LEAKAGE INDUCTANCE (@100KHZ, 0.1Vrms, 1-2, 3-4 SHORT) :
PIN 5-7 = 50uH MAX.
- TURN RATIO (@15KHZ, 1Vrms) :
PIN 1-2 : PIN 3-4 = 1 ± 1%
PIN 1-4 (2-3 SHORT) : PIN 5-7 = 1.659 ± 1%
- HI-POT : (@3000VAC, 1mA, 2SEC)
- INTERWINDING CAP. (@10KHZ, 0.1Vrms, 2-3 SHORT) :
PIN 1-5 = 40pF MAX.

						 Atech Technology Co., Ltd. TEL:0212794-6667 FAX:0212794-8004	TITLE	ISDN TRANSFORMER
							DWG. NO.	ATS-467
A	PIN 長	12/31/2002	DOLLY	AL	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
	RELEASE	08/03/00	FENG		SUEDY			
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW	Pair
REVISIONS						08/03/00		