



ELECTRICAL CHARACTERISTICS :

1. D.R.C. : 6-1 = 5.23 OHM+/-12% 12-8 = 11-7 = 11 OHM+/-12%
2. INDUCTANCE : |@1KHZ, 0.1Vrms| 12-7|W/H 8-11 SHORT| 85.5mH+/-10%
3. LEAKAGE INDUCTANCE : |@10KHZ, 0.1Vrms| 12-7|8-11,6-1 SHORT| = 170uH MAX.
4. Cw|@10KHZ, 0.1Vrms| 12-6|8-11 SHORT| = 125pF MAX.
5. TRUN RATIO : |@80KHZ, 1Vrms| 12-7|8-11 SHORT|:6-1=1.5+/-1%
6. HI-POT : |@1850VAC, 1mA, 2SEC| 12-6|8-11 SHORT|

						Atech [®]		TITLE ISDN-U TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-482	
						<small>TEL (02)2704-8867 FAX (02)2704-8004</small>			
	RELEASE	11/14/00	PAIR		SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW
REVISIONS						11/14/00		<i>Pair</i>	