



SUGGESTED PCB LAYOUT



UNIT:mm



ELECTRICAL CHARACTERISTICS :

- △ 1. DCR : PIN 3-4 = 185mΩ
PIN 1-2 = 105mΩ
PIN 5-8 = 225mΩ
2. INDUCTANCE (@2MHz, 0.1Vrms) :
PIN 5-8 = 20uH MIN.
- △ 3. TURN RATIO (@100KHz, 0.1Vrms)
PIN 5-8 : 3-4 = 1.0 ±2%
PIN 5-8 : 1-2 = 2.0 ±2%
- △ 4. HI-POT : (@1875VAC, 1mA, 1SEC) :
PIN 1,3 - PIN 5

5. RoHS COMPLIANT

								TITLE	TRANSFORMER
B	CHANGE ELECTRICAL CHARACTERISTICS	12/18/2014	SHIRLEY	RONAN	RONAN			DWG. NO.	PL-047R
A	CHANGE SCHEMATICS & ELECTRICAL CHARACTERISTICS	10/27/2014	SHIRLEY	RONAN	RONAN				
RELEASE		07/24/2014	SHIRLEY	RONAN	RONAN	UNITS:	M/M	SAFETY	SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	07/24/14	P/N:	DRAW
REVISIONS									SHIRLEY