








ELECTRICAL CHARACTERISTICS :

1. TURNS RATIO : TX/RX = 1CT : 1CT $\pm$ 3%.
2. HI-POT : 1500 Vrms.
3. L/L (@100KHz / 0.1Vrms) : 0.35uH MAX.
4. CW/W (@100KHz / 0.1Vrms) : 35pF TYP.
5. DCR: J1-J2 / J3-J6 = 1.2 Ω MAX.
6. OCL (@100KHz / 0.1Vrms, WITH 8MA DC BIAS) : 350uH MIN.
7. INSERTION LOSS (@0.1-100MHz) = -1.2 dB MAX.
8. RETURN LOSS : 1~30MHz = -18dB MIN.
40~50MHz = -15dB MIN.
60~80MHz = -12dB MIN.
9. CROSS TALK (@0.1-100MHz) = -35dB TYP.
10. CMRR (@0.1-100MHz) : -30dB TYP.
11. RoHS COMPLIANT

P.C.B RECOMMENDED HOLE LAYOUT SEEN FROM COMPONENT SIDE.
ALL CENTERLINE DIMENSIONS ARE BASIC

								TITLE	RJ45 1*1 W/ 10/100 BASE-TX TRANSFORMER
								DWG. NO.	RJC-020R
	RELEASE	07/22 /2010	SHIRLEY	BETTY	KING	UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	M/M	P/N:		
REVISIONS						07/22/10			DRAW SHIRLEY