



ELECTRICAL CHARACTERISTICS : (FOR C2161 COMPATIBLE)

- 1.D.C.R : 1-3 = 0.42 ΩHM±10% 6-4 = 1.47 ΩHM±10%
- 2.INDUCTANCE (@10KHZ,0.1Vrms) : 6-4 = 0.53mH±5%
- 3.LEAKAGE INDUCTANCE (@100KHZ,0.1Vrms) :
6-4(1-3 SHORT) = 15uH MAX.
- 4.INTERWINDING CAP. (@100KHZ,0.1Vrms) :
1-6 = 100pF MAX.
- 5.INSERTION LOSS (@100KHZ,W/H 25ΩHM LOAD) :
6-4 = 0.5dB MAX.
- 6.TURN RATIO (@1MHZ,0.1Vrms) :
6-4 : 1-3 = 2±1%
- 7.HI-POT (@600VDC,0.5mA,1SEC) 1-6

						Atech®		TITLE TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-504	
						TEL:(02)788-1958 FAX:(02)788-1960			
						MATERIAL		UNITS: M/M	
						DATE		SAFETY	
						02/12/01		SHEET 1 OF 1	
REVISIONS								DRAW <i>Pair</i>	